

elenni
Kitchen & Bathroom Collection
customerservice@elenni.com.a
07 3209 9644

meir.®

- Refer to the Meir website for warranty terms & conditions, and available finishes
- Flow rate **8 L p/m** at 3 bar pressure.
- European components and cartridge
- Solid brass construction
- Box Weight **2 kg**
- 68mm long 1/2" threaded adapter included for non-AU regions only

- Do not install tapware using any form of acetone silicones.
- Do not apply physical items (such as tools) directly to product.
- Never use house-hold or commercial detergents, citrus based cleaners, or abrasive cleaners.
- Clean using a mild washing soap solution rinsed, and dry with a soft cloth.
- Check for any product defects before installation.
- Refer to the installation manual for correct installation.

- Watermark AS/NZS3718WMKA25013
- 3-star WELS rated
- 9 Litres p/minute
- WELS registration No: S18054

Technical drawing of a shower set, showing three views: front view, side view, and top view.

Front View:

- Total height: 700
- Riser pipe height: 650
- Base width: 70
- Water inlet G1/2"

Side View:

- Showerhead diameter: 106
- Showerhead height: 235
- Connection point diameter: 32
- Distance from riser to connection point: 93
- Riser pipe diameter: Ø20
- Base diameter: Ø50

Top View:

- Showerhead width: 56
- Connection point: G1/2"
- Connection point diameter: Ø18
- Distance from riser to connection point: 26

Hose Details:

- Hose length: 1.5m
- Hose diameter: Ø45

Test pressure (MPa)	Water flow rate (Liters/min)
0.15	6.4
0.25	7.8
0.30	7.9
0.35	8.1
0.50	8.4

MAX THREAD
DEPTH 16

G1/2"

